

### Description et characteristics techniques

- Fiches Industrielles
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

### References

| REF     | Combination | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 902131A | 2P+T        | 16   | 44 | 230   | 1    | 10     |
| 902142A | 3P+T        | 16   | 44 | 400   | 1    | 10     |
| 902152A | 3P+N+T      | 16   | 44 | 400   | 1    | 10     |
| 902133A | 2P+T        | 32   | 44 | 230   | 1    | 10     |
| 902144A | 3P+T        | 32   | 44 | 400   | 1    | 10     |
| 902154A | 3P+N+T      | 32   | 44 | 400   | 1    | 10     |



| REF     | Combination | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 902431A | 2P+T        | 16   | 67 | 230   | 1    | 10     |
| 902442A | 3P+T        | 16   | 67 | 400   | 1    | 10     |
| 902452A | 3P+N+T      | 16   | 67 | 400   | 1    | 10     |
| 902433A | 2P+T        | 32   | 67 | 230   | 1    | 10     |
| 902444A | 3P+T        | 32   | 67 | 400   | 1    | 10     |
| 902454A | 3P+N+T      | 32   | 67 | 400   | 1    | 10     |



| REF     | Combination | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 902435A | 2P+T        | 63   | 67 | 230   | 1    | 10     |
| 902446A | 3P+T        | 63   | 67 | 400   | 1    | 10     |
| 902456A | 3P+N+T      | 63   | 67 | 400   | 1    | 10     |
| 902437A | 2P+T        | 125  | 67 | 230   | 1    | 10     |
| 902448A | 3P+T        | 125  | 67 | 400   | 1    | 10     |
| 902458A | 3P+N+T      | 125  | 67 | 400   | 1    | 10     |



### Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norme EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

### Characteristics Techniques

- Test do fil incandescent GWT 850°C (Glow Wire Temperature)
- Teste la boule: 125°C
- Matérielle sans halogène

