

### Description et caracteristics techniques

- Prise pour fiches coudees
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

### References

REF	Description	AMPS	IP	Volts	PACK	CARTON
931121A	2P+T	16	44	230	1	10
931142A	3P+T	16	44	400	1	10
931152A	3P+N+T	16	44	400	1	10
931123A	2P+T	32	44	230	1	10
931144A	3P+T	32	44	400	1	10
931154A	3P+N+T	32	44	400	1	10



REF	Description	AMPS	IP	Volts	PACK	CARTON
931421A	2P+T	16	67	230	1	10
931442A	3P+T	16	67	400	1	10
931452A	3P+N+T	16	67	400	1	10
931423A	2P+T	32	67	230	1	10
931444A	3P+T	32	67	400	1	10
931454A	3P+N+T	32	67	400	1	10



REF	Description	AMPS	IP	Volts	PACK	CARTON
931435A	2P+T	63	67	230	1	10
931446A	3P+T	63	67	400	1	10
931456A	3P+N+T	63	67	400	1	10
931437A	2P+T	125	67	230	1	10
931448A	3P+T	125	67	400	1	10
931458A	3P+N+T	125	67	400	1	10



REF	Description	AMPS	IP	Volts	PACK	CARTON
931131	2P+T	16	54	250	1	10
931431	2P+T	16	67	250	1	10



REF	Description	AMPS	IP	Volts	PACK	CARTON
931131F	2P+T	16	54	250	1	10

### Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norme EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

### Characteristics Techniques

- Test do fil incandescent GWT 850°C
- Teste la boule: 125°C
- Matérielle sans halogène

